THE SPLITMAX

FRAMED 72 LAYOUT MODULE



PRODUCTS	COLOR OF FRAME	POWER RANGE
TSM-DE15H(II)	Silver	385-400W

72 LAYOUT
MONOCRYSTALLINE MODULE

385-400W
POWER OUTPUT RANGE

19.7%
MAXIMUM EFFICIENCY

0~+5W
POSITIVE POWER TPLERANCE

Founded in 1997, Trina Solar is the world's leading comprehensive solutions provider for solar energy. we believe ciose cooperation with our partners is critical to success. Trina Solar now distributes its PV products to over 60 countries all over the world. Trina is able to provide exceptional service to each customer in each market and supplement our innovative, reliable products with the backing of Trina as a strong, bankable partner. We are committed to building strategic, mutually beneficial collaboration with installers, developers, distributors and other partners.

Comprehensive Products And System Certificates

IEC61215/IEC61730/UL1703/IEC61701/IEC62716
ISO 9001: Quality Management System
ISO 14001: Environmental Management System
ISO14064: Greenhouse gases Emissions Verification
OHSAS 18001: Occupation Health and Safety Management System

Trinasolar

Ideal for large scale installations

- Reduce BOS cost with higher power bin and 1500V system voltage

Half-cell design brings higher efficiency

- New cell string layout and split J-box location to reduce the energy loss caused by shading between modules
- LRF(Light Redirecting Film) integrated to gain more power
- Low thermal coefficients for greater energy production at high operating temperature
- Low cell connection power loss due to half-cell layout(144 monocrystalline)

Highly reliable due to stringent quality control

- Over 30 in-house tests (UV, TC, HF etc)
- Internal test requirement of Trina more stringent than certification authority
- PID resistant
- 100% EL double inspection

Certified to withstand the most challenging environmental conditions

- 2400 Pa negative load
- 5400 Pa positive load

LINEAR PERFORMANCE WARRANTY

10 Year Product Warranty • 25 Year Linear Power Warranty



SPLITMAX

FRAMED 72 LAYOUT MODULE

DIMENSIONS OF PV MODULE(mm)



Back View(Portrait)



Back View(Landscape)



(A-A)

I-V CURVES OF PV MODULE(390W)



P-V CURVES OF PV MODULE(390W)



ELECTRICAL DATA (STC)

Peak Power Watts-P_{MAX} (Wp)*	385	390	395	400
Power Output Tolerance-P_{MAX} (W)	0 ~ +5			
Maximum Power Voltage-V_{MPP} (V)	40.1	40.5	40.8	41.1
Maximum Power Current-I_{MPP} (A)	9.61	9.64	9.69	9.74
Open Circuit Voltage-V_{OC} (V)	48.5	49.7	50.1	50.4
Short Circuit Current-I_{SC} (A)	10.03	10.08	10.13	10.18
Module Efficiency η_m (%)	18.9	19.2	19.4	19.7

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5.
*Measuring tolerance: ±3%.

ELECTRICAL DATA (NMOT)

Maximum Power-P_{MAX} (Wp)	291	298	295	302
Maximum Power Voltage-V_{MPP} (V)	37.9	38.7	38.4	39.1
Maximum Power Current-I_{MPP} (A)	7.66	7.70	7.68	7.72
Open Circuit Voltage-V_{OC} (V)	45.6	47.1	46.8	48.0
Short Circuit Current-I_{SC} (A)	8.09	8.17	8.13	8.21

NMOT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s.

MECHANICAL DATA

Solar Cells	Monocrystalline
Cell Orientation	144 cells (6 × 24)
Module Dimensions	2024 × 1004 × 35 mm (79.69 × 39.53 × 1.38 inches)
Weight	26.4kg (58.2lb)
Glass	4.0 mm (0.16 inches), High Transmission, AR Coated Tempered Glass
Encapsulant Material	EVA
Backsheet	White
Frame	35 mm (inches) Anodized Aluminium Alloy
J-Box	IP 68 rated
Cables	Photovoltaic Technology Cable 4.0mm² (0.006 inches²), Portrait: N 140mm/P 285mm(5.51/11.22inches) Landscape: N 1400 mm /P 1400 mm (55.12/55.12 inches)
Connector	MC4 EVO2/TS4*

*Please refer to regional datasheet for specified connector.

TEMPERATURE RATINGS

NMOT(Nominal Module OperatingTemperature)	41°C (±3°C)
Temperature Coefficient of P_{MAX}	- 0.37%/°C
Temperature Coefficient of V_{OC}	- 0.29%/°C
Temperature Coefficient of I_{SC}	0.05%/°C

MAXIMUM RATINGS

Operational Temperature	-40~+85°C
Maximum System Voltage	1500V DC (IEC)
	1500V DC (UL)
Max Series Fuse Rating	20A

(DO NOT connect Fuse in Combiner Box with two or more strings in parallel connection)

WARRANTY

10 year Product Workmanship Warranty
25 year Linear Power Warranty

(Please refer to product warranty for details)

PACKAGING CONFIGURATION

Modules per box: 30 pieces
Modules per 40' container: 660 pieces

Trinasolar

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.

© 2018 Trina Solar Limited. All rights reserved. Specifications included in this datasheet are subject to change without notice.

Version number: TSM_EN_2018_A

www.trinasolar.com